

| Technical Specifications | DC06.0W-02005 | DC06.0W-08005 | DC06.0W-01005 |
|---------------------------------|----------------------|----------------------|----------------------|
| Rated Current | 55mA | 55mA | 55mA |
| Class | A+ | A+ | A+ |
| Consumption | 6kWh/1000h | 6kWh/1000h | 6kWh/1000h |
| Service Life | 20.000 hours | 20.000 hours | 20.000 hours |
| CRI | ≥ 80 | ≥ 80 | ≥ 80 |
| Power Factor | > 0.5 | > 0.5 | > 0.5 |
| Starting Time | < 1sec. | < 1sec. | < 1sec. |
| Operating Voltage Range | 100-240VAC | 100-240VAC | 100-240V |
| Rated Voltage | AC230V 50Hz | AC230V 50Hz | AC230V 50Hz |
| Rated Power | 6 W | 6 W | 6 W |
| Lumen | 420 | 420 | 450 |
| Luminous Colour | Warm White | Daylight | Cold White |
| Chrominance Signal | WW | NW | CW |
| Colour Temperature | 3000K | 4000K | 6500K |
| Body Colour | White/RAL 9016 | White/RAL 9016 | White/RAL 9016 |
| Body Material | Aluminum | Aluminum | Aluminum |
| IP Definition | IP40 | IP40 | IP40 |