

Thermal Magnetic Motor Protection Breakers (Starters)

Code No.	Nominal Power AC3 400V (kW), 50/60Hz	Thermal Setting Field [A] (40°)	Short Circuit Breaking Capacity (KA) 400V-415V	Piece in Box	Piece in Package	Gross Weight (kg)	Size of Package (mm)
69000001	0,02	0,10-0,16	100 kA	1	50	14,21	480 x 255 x 180
69000002	0,06	0,16-0,25	100 kA	1	50	14,21	480 x 255 x 180
69000003	0,09	0,25-0,40	100 kA	1	50	14,21	480 x 255 x 180
69000004	0,12	0,40-0,63	100 kA	1	50	14,21	480 x 255 x 180
69000005	0,25	0,63-1,00	100 kA	1	50	14,21	480 x 255 x 180
69000006	0,37	1,00-1,60	100 kA	1	50	14,21	480 x 255 x 180
69000007	0,75	1,60-2,5	100 kA	1	50	14,21	480 x 255 x 180
69000008	1,5	2,5-4	100 kA	1	50	14,21	480 x 255 x 180
69000009	2,2	4-6,3	100 kA	1	50	14,21	480 x 255 x 180
69000010	4	6-10	100 kA	1	50	14,21	480 x 255 x 180
69000011	5,5	9-14	15 kA	1	50	14,21	480 x 255 x 180
69000012	7,5	13-18	15 kA	1	50	14,21	480 x 255 x 180
69000013	9	17-23	15 kA	1	50	14,21	480 x 255 x 180
69000014	11	20-25	15 kA	1	50	14,21	480 x 255 x 180
69000015	15	24-32	10 kA	1	50	14,21	480 x 255 x 180



Motor Protection
Breakers

Product Name	Code No.	Technical Features	Piece in Box	Piece in Package	Gross Weight (kg)	Size of Package (mm)
--------------	----------	--------------------	-----------------	---------------------	----------------------	-------------------------

Accessories

Storage Box (Empty)	67000053	-	1	50	13,696	500 x 500 x 315
Auxiliary Contact (Mounted on Left)	67000054	1NA +1NK	1	100	5,59	467 x 200 x 157
Auxiliary Contact (Mounted on Front)	67000055	1NA +1NK	4	400	9,59	467 x 200 x 157
Shunt Release	67000057	220 V AC	1	50	5,981	465 x 290 x 74
Under Voltage	67000058	220V AC	1	50	6,181	465 x 290 x 74
Alarm Outlet Contact Release	67000059	1NA +1NK	1	100	5,49	467 x 200 x 157



Storage Box



Under Voltage
Release



Shunt Release



Alarm Outlet
Contact



Auxiliary Contact
(Mounted Left)



Auxiliary Contact
(Mounted on Front)